



C 300H
C 300H x4
C 350H
C 350H x4

6,600 – 7,700 Lbs

* Machines in photos may include some optional equipment



www.ausa.com

AUSA Center S.L.U | Ctra. de Vic, Km 2.8 - P.O.B. 194, 08243 Manresa - BARCELONA (SPAIN) Tel.: +34 93 874 73 11 E-mail: ausa@ausa.com




AUSA NORTHAMERICA CORP.
 2655 Le Jeune Road - Suite 808
 CORAL GABLES FL 33134 (USA)
 Toll free: 1 800 820 AUSA
 E-mail: ausa.corp@ausa.com

C 300H_6600 Lbs
C 350H_7700 Lbs



DIMENSIONS (ft in)	C 300 H	C 300 H x4	C 350 H	C 350 Hx4
A	7 ft 2.6 in	7 ft 2.6 in	7 ft 4.2 in	7 ft 4.2 in
B	11.8 in	11.8 in	11.8 in	11.8 in
C	1 ft 0.8 in	1 ft 0.8 in	1 ft 2.9 in	1 ft 2.9 in
D	4 ft 9.5 in	4 ft 9.5 in	4 ft 9.5 in	4 ft 9.5 in
(narrow axle) E	4 ft 11.4 in	4 ft 11.4 in	4 ft 11.4 in	4 ft 11.4 in
(wide axle) E	6 ft 4.7 in	6 ft 4.7 in	6 ft 4.7 in	6 ft 4.7 in
F	11 ft 5.7 in	15 ft 5 in	11 ft 5.7 in	15 ft 5 in
G	9 ft 4.2 in	9 ft 10.3 in	9 ft 4.2 in	9 ft 10.3 in
I	4.7 in	4.7 in	4.7 in	4.7 in
J	2 in	2 in	2 in	2 in
K	2 ft 5.5 in	2 ft 5.5 in	2 ft 5.5 in	2 ft 5.5 in
L	14 ft 9.1 in	14 ft 9.1 in	14 ft 9.1 in	14 ft 9.1 in
M	1 ft 11.6 in	1 ft 11.6 in	1 ft 11.6 in	1 ft 11.6 in
N	6 ft 4.8 in	6 ft 4.8 in	6 ft 4.8 in	6 ft 4.8 in
O	3 ft 11.2 in	3 ft 11.2 in	3 ft 11.2 in	3 ft 11.2 in
P	18 ft 4.5 in	22 ft 3.9 in	18 ft 4.5 in	22 ft 3.9 in



MastType	Maximum lift height	Front axle	Free lift	H Machine height with mast retracted				Machine height with mast extended				Load (Lbs) at max. height			
				C 300 H	C 350 H	C300Hx4	C350Hx4	C 300H	C350H	C300Hx4	C350Hx4	C 300 H	C350Hx4	C300H	C350Hx4
Triplex	22 ft 3 in	Wide	7 ft 6 in	10 ft 6 in	10 ft 6 in	10 ft 6 in	10 ft 6 in	22 ft 6 in	22 ft 6 in	22 ft 6 in	22 ft 6 in	-	1,323	-	1,323
Triplex (free lift)	17 ft 9 in	Wide	5 ft 6 in	8 ft 8 in	8 ft 10 in	8 ft 8 in	8 ft 10 in	21 ft 8 in	21 ft 8 in	21 ft 8 in	21 ft 8 in	3,307	3,527	3,307	3,527
Triplex (free lift)	12 ft 2 in	Narrow/Wide (op.)	3 ft 11 in	6 ft 10 in	7 ft	6 ft 10 in	7 ft	16 ft 1 in	16 ft 1 in	16 ft 1 in	16 ft 1 in	5,291	7,055	5,291	7,055
Duplex	13 ft 1 in	Narrow/Wide (op.)	4.7 in	9 ft 2 in	9 ft 3 in	9 ft 2 in	9 ft 3 in	17 ft 1 in	17 ft 1 in	17 ft 1 in	17 ft 1 in	4,960	6,613	4,960	4,960
Duplex (Std)	10 ft 10 in	Narrow/Wide (op.)	4.7 in	8 ft	8 ft 2 in	8 ft	8 ft 2 in	14 ft 9 in	14 ft 9 in	14 ft 9 in	14 ft 9 in	6,613	7,710	6,613	6,613

TECHNICAL SPECIFICATIONS

	C 300H	C 300H x4	C 350H	C 350H x4
Load center (Center of gravity at 24 in) (Lb)	6.614		7.716	
Max. height with mast retracted & tilted (22' triplex mast)	9 ft 2.2 in			
Max. lift at max. load capacity	10 ft 10 in			
Max. lift capacity at 22' (Lb)	4.347 (industrial terrain conditions) / 1.304 (rough terrain conditions)			
Engine	KUBOTA V 3300			
Diesel	KUBOTA V 3300			
Power acc./DIN 6270 B (KW/HP)	45.3/ 61.6 (2400 rpm)			
Power acc./DIN 70020 (KW/HP)	48.1/ 64.5 (2400 rpm)			
N° of cylinders	4			
Cooling system	Water			
Traction	4x2	4x4	4x2	4x4
Transmission	Hydrostatic with variable flow pump and automatic regulation Gear selection switch on joystick. Inching pedal			
Operating weight (Lb) (Standard version with full tanks)	11.152	12.021	11.905	12.346
Gradient negotiable (with full load)	35%	40%	35%	40%
Speed (Maximum) (Mph)	12.5			
Engine starting system	Electric			
Tires	Front	16/70 - 20	16/70 - 20	16/70 - 20
	Rear	10,0/75 - 15,3	10,0/75 - 15,3	27 x 10 - 12
Steering	Hydraulic. Working pressure 2.031PSI/ 140 bar.			
External turn radius	11 ft 5.7 in	15 ft 5 in	11 ft 5.7 in	15 ft 5 in
Tank capacity (US gal)	Fuel	21.20		
	Hydraulic fluid	17.43		
Service brake	Oil-immersed, multidisc, hydraulically driven.			
Parking brake	Oil-immersed, multidisc, spring applied and hydraulically released.			
Hydraulic circuit	30-8 cc. double gear pump.			
Operating pressures for accessories	Working pressure 2.465 PSI / 170 Bar		Working pressure 2.756 PSI / 190 Bar	

STANDARD EQUIPMENT

<ul style="list-style-type: none"> Open cab Ergonomic seat Seatbelt Joystick Rotating beacon Back up alarm Load backrest Side shift Tilting Cab for service
--

OPTIONAL EQUIPMENT

<ul style="list-style-type: none"> Semi-closed cab Full closed cab with heater Lighting system (Front and rear) Catalytic converter Spark arrestor Fuel filter / water separator 21.2, 28.3 and 35.5 Cu.ft hydraulic buckets Full closed cab with heater Wide front axle

AUSA reserves the right to make any changes in the specifications without prior notice.

AUSA MADRID 1 (SPAIN) Tel.: +34 911 669 00 06 E-mail: ausa.madrid@ausa.com AUSA FRANCE 1 Tel.: +33 (0) 4 68 54 38 97 E-mail: ausa.france@ausa.com

AUSA UK 1 Tel.: +44 (0) 1706 64 96 91 E-mail: ausa.uk@ausa.com AUSA DEUTSCHLAND GmbH. 1 (GERMANY) Tel.: +49 2385922245 E-mail: ausa.deutschland@ausa.com

BEIJING REPRESENTATIVE OFFICE 1 (CHINA) Tel: 86-10-8597 1983 - E-mail: lunafeng@ausa.com

MKT US/070307